

2SA673(A)

Rev.E Mar.-2016

/ Descriptions

TO-92 PNP Silicon PNP transistor in a TO-92 Plastic Package.


/ Features

2SC1213(A)
Complementary pair with 2SC1213(A).

/ Applications

Low frequency power amplifier.

/ Equivalent Circuit



/ Pinning



PIN1 Base PIN 2 Collector PIN 3 Emitter

/ hFE Classifications & Marking

h _{FE} Classifications Symbol	B	C	D
h _{FE} Range	60~120	100~200	160~320


/ Absolute Maximum Ratings(Ta=25)

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	2SA673 -35	V
		2SA673A -50	
Collector to Emitter Voltage	V_{CEO}	2SA673 -35	V
		2SA673A -50	
Emitter to Base Voltage	V_{EBO}	-4.0	V
Collector Current - Continuous	I_C	-500	mA
Collector Power Dissipation	P_C	400	mW
Junction Temperature	T_j	150	°C
Storage Temperature Range	T_{stg}	-55 150	°C

/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector to Base Breakdown Voltage	V_{CBO}	$I_C = -10\mu A$ $I_E = 0$	2SA673 -35			V
			2SA673A -50			
Collector to Emitter Breakdown Voltage	V_{CEO}	$I_C = -1.0mA$ $I_B = 0$	2SA673 -35			V
			2SA673A -50			
Emitter to Base Breakdown Voltage	V_{EBO}	$I_E = -10\mu A$ $I_C = 0$	-4.0			V
Collector Cut-Off Current	I_{CBO}	$V_{CB} = -20V$ $I_E = 0$			-0.5	μA
DC Current Gain	$h_{FE(1)}$	$V_{CE} = -3.0V$ $I_C = -10mA$	60		320	
	$h_{FE(2)}$	$V_{CE} = -3.0V$ $I_C = -500mA$	10			
Collector to Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = -150mA$ $I_B = -15mA$		-0.2	-0.6	V
Base to Emitter Voltage	V_{BE}	$V_{CE} = -3.0V$ $I_C = -10mA$		-0.64		V


/ Electrical Characteristic Curve




/ Package Dimensions

T0-92

Unit: mm



/ Marking Instructions



BR:

A673

B: h_{FE}

Note:


BR: Company Code.

A673: Product Type.

B: h_{FE} Classifications Symbol

****: Lot No. Code, code change with Lot No.

() / Temperature Profile for Dip Soldering(Pb-Free)



Note:

- 1

25 150

60 90sec;
- 2

255±5

5±0.5sec;
- 3

2 10

/sec.
- 1.Preheating:25~150

, Time:60~90sec.
- 2.Peak Temp.:255±5

, Duration:5±0.5sec.
3. Cooling Speed: 2~10

/sec.

/ Resistance to Soldering Heat Test Conditions

270±5 10±1 sec. Temp:270±5℃ Time:10±1 sec

/ Packaging SPEC.

/ BULK

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm3)		
	只袋	袋盒	只盒	盒箱	只箱	袋	盒	箱