


/ Descriptions


/ Features

/ Applications

/ Equivalent Circuit



/ Pinning





/ h_{FE} Classifications & Marking

BR2SD718B




DATA SHEET

/ Electrical Characteristic Curve




/ Package Dimensions




单位: mm						
Symbol	Dimensions In Millimeters		Symbol	Dimensions In Millimeters		
	Min	Max		Min	Max	
A	4.30	4.70	E	9.00	9.40	
B	1.00	1.40	e1	2.54	2.70	
C	0.50	0.60	e2	2.54	2.70	
D	10.00	10.40	L1	1.27	1.50	
L3	1.27	1.50	b1	0.50	0.60	
b2	0.50	0.60				

/ Marking Instructions



() / Temperature Profile for IR Reflow Soldering(Pb-Free)



/ Resistance to Soldering Heat Test Conditions

/ Packaging SPEC.

封装形式	包装数量					包装尺寸 :		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
TO-263	800	1	800	5	4,000	13" ×24	360×360×50	385×257×392

封装形式	包装数量					包装尺寸 :		
	Units/Tube 只/套管	Tubes/Inner Box 套管/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Tube 套管	Inner Box 盒	Outer Box 箱
TO-263	50	20	1,000	5	5,000	532×33×7.0	555×164×50	575×290×180

/ Notices