

/ Descriptions

TO-277

Schottky diode in a TO-277 Plastic Package.

/ Features


$$V_F(\text{typ})=0.26\text{V}$$

High Forward Surge Capability, Ultra Low Forward Voltage Drop $V_F(\text{typ})=0.26\text{V}$, Excellent High Temperature Stability. HF Product.


/ Applications

For use in low voltage,high frequency inverters, free wheeling, and polarity protection applications.


/ Equivalent Circuit



/ Pinning



PIN1 Anode PIN 2 Cathode PIN 3 Anode



Suggested Pad layout

/ h_{FE} Classifications & Marking

See Marking Instructions.

/ Absolute Maximum Ratings(Ta=25)

Parameter	Symbol	Rating	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage Peak Reverse Voltage	V_{RRM} V_{RWM} V_{RM}	45	V
RMS Reverse voltage	$V_{R(RMS)}$	42	V
Average Rectified Output Current	I_O	10	A
Non-Repetitive Peak Forward Surge Current	I_{FSM}	275	A
Repetitive peak avalanche power	P_{ARM}	30000	W
Junction Temperature Range	T_j $V_R \leq 80\% V_{RRM}$	150	°C
Storage Temperature Range	T_{stg}	-55 150	°C
Typical Thermal Resistance	$R_{\theta JA}$ Note 1	73	°C/W

/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Reverse Voltage	V_R	$I_R=0.3mA$	45			V
Forward voltage	V_F	$I_F=2A$ $T_J=25^\circ C$		0.39	0.43	V
		$I_F=2A$ $T_J=125^\circ C$		0.26		V
		$I_F=10A$ $T_J=25^\circ C$		0.49	0.52	V
		$I_F=10A$ $T_J=125^\circ C$		0.41	0.44	V
Instantaneous Reverse Current	I_R Note 2	$V_R=45V$ $T_J=25^\circ C$		3	15	uA
		$V_R=45V$ $T_J=100^\circ C$			5	mA
		$V_R=45V$ $T_J=125^\circ C$			10	mA

/Notes

1. FR-4 PCB 2

/FR-4 PCB, 2oz. Copper, minimum recommended pad


layout per.

2.


/Short duration pulse test used to minimize self-heating

effect.

/ Electrical Characteristic Curve



/ Package Dimensions



/ Marking Instructions



10L45

Note:


10L45

Product Type.

****:

Lot No. Code, code change with Lot No.

() /



Note:

- | | | | | | |
|---|-------|-----|-----------|--------|---|
| 1 | 150 | 180 | 60 | 90sec; | 1.Preheating:150~180 , Time:60~90sec. |
| 2 | 245±5 | | 5±0.5sec; | | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 | | 2 | 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

260±5	10±1 sec.	Temp.:260±5℃	Time:10±1 sec
-------	-----------	--------------	---------------

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量 Units/Reel2&	Dimension 包装尺寸 (unit: mm ³)
----------------------	----------------------------	---