



/ Descriptions

SOT-363 Y Z Z 2 [NPN \] ^ _ ` a M

Double silicon NPN transistor in a SOT-363 Plastic Package.

/ Features

b c d e f , g h MMDT5401 i j M F G k l M


High voltage, complementary pair with MMDT5401. HF Product.

/ Applications


m n o p f e q r M

General purpose high voltage amplifier.

/ Equivalent Circuit



/ Pinning




PIN1 s 4 t Emitter

PIN 2 s 5 t Base

PIN 3 s 6 t Collector



/ h_{FE} Classifications & Marking

See Marking Instructions.




u v Parameter	w x Symbol	v y Rating	z { Unit
Collector to Base Voltage	V_{CBO}	180	V
Collector to Emitter Voltage	V_{CEO}	160	V
Emitter to Base Voltage	V_{EBO}	6.0	V
Collector Current	I_C	600	mA
Base Current	I_B	300	mA
Collector Power Dissipation		500	mW
Junction Temperature		150	°C
Storage Temperature Range		-55 ~ 150	°C


/ Electrical Characteristic Curve



/ Package Dimensions



/ Marking Instructions



! § t

● t " ©1^a «

G1 t " ¥ X ¬ '

***: $\mathbb{R}^k \times \mathbb{R}^k \rightarrow \mathbb{R}^k$


Note:

● t "1" Pin

G1 t	Product Type Code
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
10	10
11	11
12	12
13	13
14	14
15	15
16	16
17	17
18	18
19	19
20	20
21	21
22	22
23	23
24	24
25	25
26	26
27	27
28	28
29	29
30	30
31	31
32	32
33	33
34	34
35	35
36	36
37	37
38	38
39	39
40	40
41	41
42	42
43	43
44	44
45	45
46	46
47	47
48	48
49	49
50	50
51	51
52	52
53	53
54	54
55	55
56	56
57	57
58	58
59	59
60	60
61	61
62	62
63	63
64	64
65	65
66	66
67	67
68	68
69	69
70	70
71	71
72	72
73	73
74	74
75	75
76	76
77	77
78	78
79	79
80	80
81	81
82	82
83	83
84	84
85	85
86	86
87	87
88	88
89	89
90	90
91	91
92	92
93	93
94	94
95	95
96	96
97	97
98	98
99	99
100	100

***: Lot No. Code, code change with Lot No.

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- | | | | | | |
|---|-------|-----|-----------|--------|--|
| 1 | 150 | 180 | 60 | 90sec; | 1.Preheating:150~180°C, Time:60~90sec. |
| 2 | 245±5 | | 5±0.5sec; | | 2.Peak Temp.:245±5°C, Duration:5±0.5sec. |
| 3 | | 2 | 10°C/sec. | | 3. Cooling Speed: 2~10°C/sec. |

/ Resistance to Soldering Heat Test Conditions

260±5°C

10±1 sec.

Temp.:260±5°C

Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT-363	3,000	10	30,000	6	180,000	7" ×8	180×120×180	390×385×205

/ Notices